



# Dryvit TAFS™

SUPERIOR FINISH SOLUTIONS

TEXTURED ACRYLIC FINISH SYSTEMS



An RPM Company

# Dryvit TAFS: High Performance Finish

## Exterior Wall Construction

THERE ARE MANY WAYS TO BUILD AN EXTERIOR WALL. WOOD OR STEEL FRAMING, WITH SHEATHING AND CLADDING, IS THE PRIMARY METHOD USED IN MOST RESIDENTIAL AND COMMERCIAL CONSTRUCTION IN NORTH AMERICA. HOWEVER, OTHER SYSTEMS AND MATERIALS, BOTH STRUCTURAL AND NON-STRUCTURAL, ARE GAINING MARKET SHARE EACH YEAR. MANY OF THESE NEWER SYSTEMS REQUIRE AND CAN ACCOMMODATE A NUMBER OF DIVERSE EXTERIOR FINISH OPTIONS. DURABLE, ATTRACTIVE AND AFFORDABLE, DRYVIT TAFS MEET THE NEEDS OF THIS GROWING MARKET SEGMENT.

## What is TAFS?

TAFS REFERS TO THE COMBINATION OF DRYVIT PRODUCTS THAT MAY BE APPLIED TO AN EXTERIOR WALL IN A NON-EIFS ASSEMBLY. UNLIKE EXTERIOR INSULATION AND FINISH SYSTEMS (EIFS), TAFS DOES NOT CONTAIN AN INSULATING COMPONENT. USING TAFS, THE DESIGN PROFESSIONAL OR BUILDER CAN SPECIFY A DIRT PICKUP RESISTANT, DURABLE, HIGH PERFORMANCE EXTERIOR THAT IS MANUFACTURED TO BE COMPATIBLE WITH THE TYPE OF CONSTRUCTION USED. TAFS IS AN EXCELLENT OPTION FOR STUCCO, CONCRETE MASONRY UNITS, TILT UP, ICF, AND OTHER COMPATIBLE SUBSTRATES THAT MAY BE APPROVED ON A CASE BY CASE BASIS BY DRYVIT'S ENGINEERING DEPARTMENT.

## Design Options

DRYVIT'S VAST ARRAY OF FINISHES CAN BE INCORPORATED INTO ANY TAFS. WHETHER THE DESIRED LOOK IS BRICK, STUCCO, LIMESTONE, GRANITE OR COMBINATIONS THEREOF... DRYVIT HAS A BEAUTIFUL, DURABLE, LIGHTWEIGHT, AND COST EFFICIENT OPTION. CUSTOM COLORS ARE AVAILABLE IN ALL FINISHES, AND DECORATIVE EPS SHAPES CAN BE USED TO ADD A THIRD DIMENSION TO AN OTHERWISE FLAT, DRAB WALL. THINK OF DRYVIT TAFS AS THE PERFECT WAY TO FINISH THE WALL.



CUSTOM BRICK™



LYMESTONE™



TERRA NEO®



TUSCAN GLAZE™



AMERISTONE™



SANDPEBBLE®



STONE MIST®



METALLIC  
DEMANDIT®

COVER: KHS&S OFFICE BUILDING, TAMPA, FL  
TAFS OVER TILT-UP CONSTRUCTION

# Solutions For Exterior Walls

## Textured Acrylic Finish Systems

### System 1

SYSTEM 1 CONSISTS OF DRYVIT TINTED PRIMER AND FINISH, AND IS USED PRIMARILY OVER RIGID, HIGHLY IMPACT-RESISTANT WALLS, SUCH AS CONCRETE OR STUCCO. OTHER SURFACES MAY BE APPROVED BY DRYVIT'S ENGINEERING DEPARTMENT. FOR SUPERIOR RESULTS, TINTED PRIMER IS NECESSARY TO MINIMIZE THE MIGRATION OF EFFLORESCENCE FROM THE CEMENT IN THE WALL ASSEMBLY ITSELF, THROUGH THE ACRYLIC FINISH COAT. AT THE SAME TIME, THE PRIMER ENHANCES ADHESION OF THE FINISH AS WELL AS THE AESTHETIC UNIFORMITY OF THE FINISHED WALL.



### System 2

SYSTEM 2 CONSISTS OF DRYVIT BASE COAT, FIBERGLASS REINFORCING MESH, TINTED PRIMER AND FINISH. THIS COMBINATION MUST ALWAYS BE USED OVER SUBSTRATES SUCH AS INSULATED CONCRETE FORMS AND EPS SHAPES. SYSTEM 2 PROVIDES IMPACT AND CRACK RESISTANCE TO THESE SURFACES. SYSTEM 2 IS ALSO COMMONLY USED TO ENHANCE THE AESTHETIC QUALITY AS WELL AS CRACK RESISTANCE OF STUCCO WALLS.

DRYVIT TAFS ARE ALSO EXTENSIVELY USED IN RENOVATING EXISTING WALLS OF VARIOUS CONSTRUCTION TYPES, INCLUDING RESTORATION OF EIFS.



SUBSTRATE	SYSTEM 1	SYSTEM 2
EXPANDED POLYSTYRENE SHAPES (EPS)	NO	YES
INSULATED CONCRETE FORMS (ICF)	NO	YES
CEMENT PLASTER (STUCCO)	YES	YES
CONCRETE MASONRY UNITS (CMU)	NO	YES
TILT-UP/PRECAST CONCRETE	YES	YES
EXTERIOR CEMENT BOARD*	NO	YES
UNGLAZED BRICK	NO	YES

For other applications, contact Dryvit Systems, Inc.

Dryvit TAFS products come with a 10-year limited materials warranty. For further information, contact Dryvit Systems, Inc.

\* PER DRYVIT'S SPECIFICATIONS FOR USE IN CEMENT BOARD MD SYSTEM, DS 191

BEFORE YOU BEGIN,  
CONSIDER THE FINISH.



## **TAFS** – applied by craftsmen to almost any wall surface!

DRYVIT IS SOLD NATIONWIDE THROUGH A STRATEGICALLY PLACED NETWORK OF AUTHORIZED DISTRIBUTORS, WHO CAN PROVIDE ADDITIONAL INFORMATION AND SAMPLES. TAFS ARE EASILY APPLIED BY PROFESSIONAL CONTRACTORS, USING A VARIETY OF TECHNIQUES, TO ACHIEVE THE FINAL DESIRED APPEARANCE. A JOB MOCK UP USING THE WALL TYPE AND PRODUCTS SPECIFIED IS ALWAYS RECOMMENDED. FOR MORE INFORMATION AND LOCATION OF YOUR NEAREST DRYVIT DISTRIBUTOR, CALL DRYVIT TECHNICAL SERVICES AT 800.556.7752 OR VISIT [WWW.DRYVIT.COM](http://WWW.DRYVIT.COM)

Information contained in this brochure conforms to the standard detail recommendations and specifications for the installation of Dryvit Systems, Inc. products as of the date of publication of this document and is presented in good faith. Dryvit Systems, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Dryvit Systems, Inc.

**dryvit**® 

An **RPM** Company

Dryvit Systems, Inc.  
One Energy Way  
P. O. Box 1014  
West Warwick, RI 02893  
800-556-7752  
401-822-4100  
[www.dryvit.com](http://www.dryvit.com)

© Dryvit Systems, Inc. 2006  
Printed in U.S.A. 2-06-5M