

DETAIL

OMD.01	OUTSULATION MD SYSTEM
OMD.02	OUTSULATION MD SYSTEM WITH AQUADUCT OPTION
OMD.03	OUTSULATION MD BOARD PROFILE & ADHESIVE PATTERN
OMD.04	BUILDING FACADE - AQUADUCT / PE OPTION SHOWN
OMD.05	OUTSIDE CORNER - R.S. BOARD LAYOUT
OMD.06	COMPARTMENT SEPARATION - PE OPTION SHOWN
OMD.07	FOUNDATION
OMD.08	TERMINATION AT CONCRETE
OMD.09	PROTECTION OF ROUGH OPENINGS
OMD.10A	HEAD / SILL - FOR WINDOW SPANS LESS THAN 10' (3M)
OMD.10B	HEAD / SILL - FOR WINDOW SPANS 10' (3M) OR GREATER
OMD.11	JAMB
OMD.12	PARAPET - CAP FLASHING
OMD.13	PARAPET - SOLID SUBSTRATE, METAL COPING
OMD.14	SOFFIT / FASCIA INTERSECTION
OMD.15	INSIDE / OUTSIDE CORNERS
OMD.16	OUTSIDE CORNER - HIGH IMPACT
OMD.17	HORIZONTAL EXPANSION JOINT
OMD.18	HORIZONTAL SLIP JOINT
OMD.19	HORIZONTAL SLIP JOINT - EXTENDED 2D VIEW
OMD.20	HORIZONTAL SLIP JOINT - OPEN SEALANT WITH FLASHING OPTION
OMD.21	TWO-STAGE JOINT
OMD.22	STRUCTURAL EXPANSION JOINTS
OMD.23	PENETRATIONS - CROSS SECTION
OMD.24	INSULATION LAYOUT - OPENINGS
OMD.25	SIGN ATTACHMENT
OMD.26	AESTHETIC REVEALS
OMD.27	PROJECTING GRAPHICS
OMD.28	RECESSED GRAPHICS

NOTE

DRYVIT MAKES NO REPRESENTATION REGARDING CONFORMITY OF ITS SUGGESTIONS TO APPLICABLE BUILDING CODES, ENGINEERING CRITERIA, SPECIFIC APPLICATIONS OR PROJECT LOCATIONS. ALL COMPONENTS INDICATED IN ILLUSTRATIONS, AS WELL AS OTHERS THAT MAY BE REQUIRED FOR THE INTEGRITY OF THE SYSTEM SHALL BE DESIGNED, DETAILED AND ENGINEERED BY REPRESENTATIVES OF THE ARCHITECT, OWNER OR CONTRACTOR TO BE IN CONFORMANCE WITH MODEL CODES, ARCHITECTURAL AND ENGINEERING REQUIREMENTS PERTAINING TO SPECIFIC BUILDING PROJECTS.

DRYVIT MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ARCHITECTURAL DESIGN, ENGINEERING, OR WORKMANSHIP OF PROJECTS UTILIZING DRYVIT SYSTEMS OR PRODUCTS.

THE LIABILITIES OF DRYVIT SHALL BE AS STATED IN THE OUTSULATION® MD LIMITED COMMERCIAL WARRANTY. CONTACT DRYVIT FOR A FULL AND COMPLETE COPY OF THE WARRANTY.