

J-TRACK ATTACHED WITH DRYVIT AP ADHESIVE (SEE NOTE 2 AND 3)

REFER TO OPMD 3, OPMD 3A, OPMD 4, OPMD 5, OPMD 5A

DRYVIT AQUAFASH® SYSTEM, DRYVIT BACKSTOP® FLASH AND FILL, TREMCO DYMONIC 100 OR TREMCO EXOAIR 230 WITH TREMCO 2011 MESH (SEE NOTES 4,5)

DRYVIT AQUAFASH® SYSTEM, DRYVIT BACKSTOP® NTX™ - TEXTURE OVER DRYVIT GRID TAPE™, DRYVIT BACKSTOP® FLASH AND FILL OR TREMCO DYMONIC 100 (SEE NOTES 4,5)

SEALANT, BY OTHERS

NOTE:

1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD OR STANDARD PLUS MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.

2. LIGHTLY SAND SURFACE OF J-TRACK TO MAXIMIZE ADHESION.


3. LENGTH OF TRACK NOT TO EXCEED 10 FT. (3.0 M)

4. REFER TO PRODUCT DATA SHEETS FOR SPECIFIC APPLICATION METHODS.

5. THE ONLY WRB TO BE USED WITH BACKSTOP® FLASH AND FILL IS BACKSTOP® NTX™.

*The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.*

**Outsulation® Plus MD System®**

|   |                             |                |            |              |            |  |   |
|---|-----------------------------|----------------|------------|--------------|------------|--|---|
|                         | Detail: Head J-Track Option |                |            |              | File Name: |  |  |
|   | Drawn by: KAB               | Checked by: CB | Scale: NTS | Date: 2/2022 | OPMD 15    |  |   |
| <p>Dryvit Technical Support: 800-556-7752</p> <p>www.tremcocpg.com</p> <p>Construction Products Group</p> |                             |                |            |              |            |  |   |