

Table of Contents

Detail

| | |
|---|----------|
| OUTSULATION PLUS MD SYSTEM | OPMD 1 |
| OUTSULATION PLUS MD SYSTEM STARTER BOARD OPTION | OPMD 1a |
| AWRB APPLICATION | OPMD 2 |
| OPENING PREPARATION- AQUAFASH® SYSTEM OR EXOAIR 230 WITH MESH OPTION | OPMD 3 |
| OPENING PREPARATION - DYMONIC 100/BACKSTOP® FLASH AND FILL OPTION | OPMD 3a |
| OPENING PREPARATION- BACKSTOP® NTX™ OPTION | OPMD 4 |
| OPENING FLASHING INTEGRATION | OPMD 5 |
| OPENING FLASHING INTEGRATION- DYMONIC 100/ BACKSTOP FLASH AND FILL OPTION | OPMD 5a |
| INSIDE/OUTSIDE CORNERS | OPMD 6 |
| INSIDE/OUTSIDE CORNERS - DYMONIC 100/ BACKSTOP FLASH AND FILL OPTION | OPMD 6a |
| OUTSIDE CORNER - HIGH IMPACT | OPMD 7 |
| GRADE TERMINATION | OPMD 8 |
| TERMINATION AT CONCRETE CURB | OPMD 9 |
| TERMINATION AT ADA COMPLIANT SIDEWALK | OPMD 10 |
| TERMINATION AT ADA COMPLIANT SIDEWALK - TREMCO OPTION | OPMD 10a |
| EPS PREPARATION AT WALL PENETRATIONS | OPMD 11 |
| STOREFRONT WINDOW SILL - JAMB | OPMD 12 |
| SELF FLASHING WINDOW SILL - JAMB | OPMD 13 |
| STOREFRONT AND FLANGED WINDOW HEAD | OPMD 14 |
| HEAD J-TRACK OPTION | OPMD 15 |
| TERMINATION AT WOOD FRAMED DECK | OPMD 16 |
| TERMINATION AT WATERPROOF DECK | OPMD 17 |
| PREPARATION AT PARAPET/ WALL INTERSECTION | OPMD 18 |
| TERMINATION AT PARAPET - CAP FLASHING | OPMD 19 |
| TERMINATION AT PARAPET - SOLID SUBSTRATE | OPMD 20 |
| TERMINATION AT PARAPET - SOLID SUBSTRATE - DYMONIC 100/ | OPMD 20a |

Detail

| | |
|---|----------|
| BACKSTOP FLASH AND FILL TERMINATION AT SLOPED ROOF | OPMD 21 |
| TERMINATION AT ROOF STOP FLASHING | OPMD 22 |
| VERTICAL WALL/ SUSPENDED SOFFIT TRANSITION | OPMD 23 |
| TRANSITION AT SOFFIT/ FASCIA INTERSECTION | OPMD 24 |
| FASCIA/ UNINSULATED SOFFIT TRANSITION | OPMD 25 |
| TERMINATION AT UNINSULATED SOFFIT VENT | OPMD 26 |
| HORIZONTAL SLIP JOINT WITHOUT WEEPS | OPMD 27 |
| HORIZONTAL SLIP JOINT WITH WEEPS | OPMD 28 |
| HORIZONTAL SLIP JOINT WITH WEEPS-DYMONIC SIMPLE SEAL | OPMD 28a |
| HORIZONTAL JOINT - SUBSTRATE CHANGE | OPMD 29 |
| HORIZONTAL TERMINATION AT STONE VENEER | OPMD 30 |
| HORIZONTAL TERMINATION AT STUCCO | OPMD 31 |
| HORIZONTAL TERMINATION AT WOOD SIDING | OPMD 32 |
| VERTICAL EXPANSION JOINT - EIFS | OPMD 33 |
| THROUGH-WALL EXPANSION JOINT | OPMD 34 |
| THROUGH-WALL EXPANSION JOINT DYMONIC SIMPLE SEAL | OPMD 34a |
| VERTICAL EXPANSION JOINT - FLUSH OPTION | OPMD 35 |
| VERTICAL EXPANSION JOINT - RECESSED OPTION | OPMD 36 |
| VERTICAL EXPANSION JOINT - DOUBLE SEAL OPTION | OPMD 37 |
| VERTICAL TERMINATION AT STONE VENEER | OPMD 38 |
| PENETRATIONS | OPMD 39 |
| SIGN ATTACHMENT | OPMD 40 |
| AESTHETIC REVEALS | OPMD 41 |
| RECESSED GRAPHICS | OPMD 42 |
| PROJECTING GRAPHICS | OPMD 43 |
| EPS SHAPES | OPMD 44 |

NOTE:

DRYVIT AND TREMCO MAKES NO REPRESENTATION REGARDING CONFORMITY OF ITS SUGGESTIONS TO MODEL BUILDING CODES, ENGINEERING CRITERIA, SPECIFIC APPLICATIONS, OR PROJECT LOCATIONS. ALL COMPONENTS INDICATED IN ILLUSTRATIONS, AS WELL AS OTHERS THAT MAY BE REQUIRED FOR THE INTEGRITY OF THE SYSTEM SHALL BE DESIGNED, DETAILED, AND ENGINEERED BY REPRESENTATIVES OF THE ARCHITECT, OWNER, OR CONTRACTOR TO BE IN CONFORMANCE WITH MODEL CODES, ARCHITECTURAL, AND ENGINEERING REQUIREMENTS PERTAINING TO SPECIFIC BUILDING PROJECTS.

DRYVIT AND TREMCO MAKE NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ARCHITECTURAL DESIGN, ENGINEERING, OR WORKMANSHIP OF PROJECTS UTILIZING DRYVIT SYSTEMS OR PRODUCTS.

THE LIABILITIES OF DRYVIT AND TREMCO SHALL BE AS STATED IN THE DRYVIT STANDARD WARRANTY. CONTACT DRYVIT AND TREMCO FOR A FULL AND COMPLETE COPY OF THE WARRANTY.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

Outsulation® Plus MD System®



Dryvit Technical Support: 800-556-7752

Detail: Table of Contents

Drawn by: KAB

Checked by: CB

Scale: NTS

Date: 2/2022

File Name:

TOC



Construction Products Group

www.tremcocpg.com