

Table of Contents

Detail

OUTSULATION PE SYSTEM	OPE 0.0.01
BUILDING FACADE	OPE 0.0.02
EPS INSULATION BOARD LAYOUT	OPE 0.0.03
OUTSIDE CORNER - EPS INSULATION BOARD LAYOUT	OPE 0.0.04
EPS INSULATION BOARD - GROOVE PATTERN	OPE 0.0.05
DRYVIT VENT ASSEMBLY™	OPE 0.0.06
COMPARTMENT SEPARATION	OPE 0.0.07
DRYVIT/TREMCO AWRB APPLICATION	OPE 0.0.08
OPENING PREPARATION - DRYVIT AQUAFLASH® SYSTEM OR TREMCO EXOAIR 230 WITH MESH OPTION	OPE 0.0.09
OPENING PREPARATION - TREMCO DYMONIC 100 OR DRYVIT BACKSTOP® FLASH AND FILL OPTION	OPE 0.0.10
OPENING PREPARATION - DRYVIT BACKSTOP® NTX™ AT HEAD AND JAMB OPTION	OPE 0.0.11
OPENING FLASHING INTEGRATION - DRYVIT AQUAFLASH® SYSTEM OPTION	OPE 0.0.12
OPENING FLASHING INTEGRATION - TREMCO DYMONIC 100 OR DRYVIT BACKSTOP FLASH AND FILL OPTION	OPE 0.0.13
FOUNDATION	OPE 0.0.14
TERMINATION AT CONCRETE	OPE 0.0.15
HEAD/SILL	OPE 0.0.16
JAMB	OPE 0.0.17
PARAPET - STEEL FRAMED WITH METAL COPING	OPE 0.0.18
PARAPET - SOLID SUBSTRATE WITH METAL COPING	OPE 0.0.19
PARAPET - SOLID SUBSTRATE WITH METAL COPING - TREMCO EXOAIR 110AT WITH DYMONIC 100	OPE 0.0.19a
INSIDE/OUTSIDE CORNERS	OPE 0.0.20
INSIDE/OUTSIDE CORNERS - TREMCO DYMONIC 100	OPE 0.0.21
OUTSIDE CORNER - HIGH IMPACT	OPE 0.0.22
HORIZONTAL EXPANSION JOINT	OPE 0.0.23
HORIZONTAL SLIP JOINT	OPE 0.0.24
VERTICAL EXPANSION JOINT OPTIONS	OPE 0.0.25
STRUCTURAL EXPANSION JOINTS - DRYVIT AQUAFLASH® SYSTEM OPTION	OPE 0.0.26
STRUCTURAL EXPANSION JOINTS - TREMCO DYMONIC SIMPLE SEAL OPTION	OPE 0.0.26a
MINOR PENETRATIONS	OPE 0.0.27
MAJOR PENETRATIONS	OPE 0.0.28
SIGN ATTACHMENT	OPE 0.0.29
AESTHETIC REVEALS	OPE 0.0.30
PROJECTING GRAPHICS	OPE 0.0.31
RECESSED GRAPHICS	OPE 0.0.32

NOTE:

DRYVIT AND TREMCO MAKES NO REPRESENTATION REGARDING CONFORMITY OF ITS SUGGESTIONS TO MODEL BUILDING CODES, ENGINEERING CRITERIA, SPECIFIC APPLICATIONS, OR PROJECT LOCATIONS. ALL COMPONENTS INDICATED IN ILLUSTRATIONS, AS WELL AS OTHERS THAT MAY BE REQUIRED FOR THE INTEGRITY OF THE SYSTEM SHALL BE DESIGNED, DETAILED, AND ENGINEERED BY REPRESENTATIVES OF THE ARCHITECT, OWNER, OR CONTRACTOR TO BE IN CONFORMANCE WITH MODEL CODES, ARCHITECTURAL, AND ENGINEERING REQUIREMENTS PERTAINING TO SPECIFIC BUILDING PROJECTS.

DRYVIT AND TREMCO MAKE NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ARCHITECTURAL DESIGN, ENGINEERING, OR WORKMANSHIP OF PROJECTS UTILIZING DRYVIT SYSTEMS OR PRODUCTS.

THE LIABILITIES OF DRYVIT AND TREMCO SHALL BE AS STATED IN THE DRYVIT STANDARD WARRANTY. CONTACT DRYVIT AND TREMCO FOR A FULL AND COMPLETE COPY OF THE WARRANTY.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

Outsulation® PE System™



Dryvit Technical Support: 800-556-7752

Detail: Table of Contents

Drawn by: SMS

Checked by: CB

Scale: NTS

Date: 1/2022

File Name:

OPE TOC



Construction Products Group

www.tremcocpg.com