



**TREMCO DYMONIC
SIMPLE SEAL OPTION**

SECTION A-A

- NOTE:
1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD™ OR STANDARD PLUS™ MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
 2. LOCATE EXTERNAL SEALANT JOINT A MAXIMUM OF 2"(51 MM) BELOW BREAK IN SUBSTRATE.
 3. LIGHTLY SAND SURFACE OF DRAINAGE TRACK TO MAXIMIZE ADHESION.
 4. DRYVIT VENT ASSEMBLY IS INSTALLED ONLY AT PUNCHOUT IN DRYVIT VENT TRACK.
 5. BOTTOM OF VENT ASSEMBLY MUST REMAIN OPEN TO DRAIN.
 6. REFER TO PRODUCT DATA SHEETS FOR SPECIFIC APPLICATION METHODS.
 7. THE ONLY WRB TO BE USED WITH BACKSTOP FLASH AND FILL IS BACKSTOP® NTX™

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

Outsulation® PE System™

 <p>Dryvit Technical Support: 800-556-7752</p>	Detail: Horizontal Slip Joint				File Name:	 <p>Construction Products Group</p>
	Drawn by: SMS	Checked by: CB	Scale: NTS	Date: 1/2022	OPE 24	
www.tremcocpg.com						