

TABLE OF CONTENTS

OUTSULATION® PLUS MD SYSTEM®

Over 1/2" Gypsum, DensGlass Gold, Securock or e2XP (30 feet or less)	NOA 17-0807.17
Over 5/8" DensGlass Gold, Securock or e2XP (30 feet or less)	NOA 17-0807.16
Over ASTM C 1177 Sheathing (above 30 feet)	NOA 18-0123.09
Over 5/8" e2XP (30 feet or less)	NOA 18-0123.10
Over 5/8" e2XP (30 feet or less)	NOA 18-0123.11
Over Concrete or Concrete Block	NOA 17-0807.13
Over ASTM C 1177 Sheathing	NOA 19-0808.01
Over Plywood	NOA 17-0807.19

OUTSULATION® SYSTEM

Over 5/8" DensGlass Gold, Securock or e2XP (30 feet or less)	NOA 18-0123.12
Over 1/2" Gypsum, DensGlass Gold, Securock or e2XP (30 feet or less)	NOA 17-0807.14
Over 5/8" e2XP (30 feet or less)	NOA 18-0123.10
Over 5/8" e2XP (30 feet or less)	NOA 18-0123.11
Over Gypsum, DensGlass Gold or Securock (above 30 feet)	NOA 17-0807.15
Over ASTM C 1177 Sheathing (above 30 feet)	NOA 18-0123.09
Over Concrete or Concrete Block	NOA 17-0807.13
Over ASTM C 1177 Sheathing	NOA 19-0808.01

OUTSULATION® X SYSTEM

Over 5/8" ASTM C 1177 Sheathing	NOA 17-0807.18
---------------------------------	----------------

NOTE

DRYVIT MAKES NO REPRESENTATION REGARDING CONFORMITY OF ITS SUGGESTIONS TO MODEL BUILDING CODES, ENGINEERING CRITERIA, SPECIFIC APPLICATIONS, OR PROJECT LOCATIONS. ALL COMPONENTS INDICATED IN ILLUSTRATIONS, AS WELL AS OTHERS THAT MAY BE REQUIRED FOR THE INTEGRITY OF THE SYSTEM SHALL BE DESIGNED, DETAILED, AND ENGINEERED BY REPRESENTATIVES OF THE ARCHITECT, OWNER, OR CONTRACTOR TO BE IN CONFORMANCE WITH MODEL CODES, ARCHITECTURAL, AND ENGINEERING REQUIREMENTS PERTAINING TO SPECIFIC BUILDING PROJECTS.

DRYVIT MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ARCHITECTURAL DESIGN, ENGINEERING, OR WORKMANSHIP OF PROJECTS UTILIZING DRYVIT SYSTEMS OR PRODUCTS.

THE LIABILITIES OF DRYVIT SHALL BE AS STATED IN THE SYSTEM'S LIMITED COMMERCIAL WARRANTY. CONTACT DRYVIT FOR A FULL AND COMPLETE COPY OF THE WARRANTY.

THE ARCHITECTURE, ENGINEERING, AND DESIGN OF THE PROJECT USING THE DRYVIT PRODUCTS IS THE RESPONSIBILITY OF THE PROJECT'S DESIGN PROFESSIONAL. ALL SYSTEMS MUST COMPLY WITH LOCAL BUILDING CODES AND STANDARDS. THIS DETAIL IS FOR GENERAL INFORMATION AND GUIDANCE ONLY AND DRYVIT SPECIFICALLY DISCLAIMS ANY LIABILITY FOR THE USE OF THIS DETAIL AND FOR THE ARCHITECTURE, DESIGN, ENGINEERING OR WORKMANSHIP OF ANY PROJECT. THE PROJECT DESIGN PROFESSIONAL DETERMINES, IN ITS SOLE DISCRETION, WHETHER THIS DETAIL OR A FUNCTIONALLY EQUIVALENT DETAIL IS BEST SUITED FOR THE PROJECT. USE OF A FUNCTIONALLY EQUIVALENT DETAIL DOES NOT VIOLATE DRYVIT'S WARRANTY. THIS DETAIL IS SUBJECT TO CHANGE WITHOUT NOTICE. CONTACT DRYVIT TO ENSURE YOU HAVE THE MOST RECENT VERSION.

Dryvit Outsulation® Systems

Meeting Hurricane Zone, High-Velocity Impact Requirements

