



## Fedderlite<sup>®</sup> Panel System

## Fedderlite Panel System

**NOTE:**

1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER<sup>®</sup> MESH PRIOR TO STANDARD OR STANDARD PLUS<sup>™</sup> MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
2. FOR FACE FASTENING, ALLOW CHANNELS TO EXTEND PAST PANEL EDGES MINIMUM 1/2" (12mm).

3. WHEN INSTALLATION RESULTS IN A CONTINUOUS AIR SPACE BETWEEN THE PANEL AND THE WALL GREATER THAN 1/8" (3mm), THE ENTIRE PANEL NEEDS TO BE ENCAPSULATED WITH THE REINFORCED BASE COAT.

The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, or engineering of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. Use of a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.