

Table of Contents

Detail

OUTSULATION MD SYSTEM	OMD 1
BUILDING FACADE	OMD 2
DRYVIT VENT ASSEMBLY™	OMD 3
INSULATION BOARD	OMD 4
INSULATION BOARD LAYOUT	OMD 5
AWRB APPLICATION	OMD 6
OPENING PREPARATION-	OMD 7
AQUAFLASH® SYSTEM OR	
EXOAIR 230 WITH MESH	
OPENING PREPARATION-	OMD 7a
DYMONIC 100/BACKSTOP®	
FLASH AND FILL OPTION	
OPENING PREPARATION-	OMD 8
BACKSTOP® NTX™ OPTION	
OPENING FLASHING INTEGRATION	OMD 9
OPENING FLASHING INTEGRATION -	OMD 9a
DYMONIC 100/BACKSTOP®	
FLASH AND FILL OPTION OPTION	
INSIDE/OUTSIDE CORNERS	OMD 10
INSIDE/OUTSIDE CORNERS-	OMD 10a
DYMONIC 100/BACKSTOP®	
FLASH AND FILL OPTION OPTION	
OUTSIDE CORNER - HIGH IMPACT	OMD 11
GRADE TERMINATION	OMD 12
TERMINATION AT CONCRETE CURB	OMD 13
TERMINATION AT	OMD 14
ADA COMPLIANT SIDEWALK	
TERMINATION AT	OMD 14a
ADA COMPLIANT SIDEWALK-	
TREMCO OPTION	
EPS PREPARATION AT	OMD 15
WALL PENETRATIONS	
STOREFRONT WINDOW SILL - JAMB	OMD 16
STOREFRONT WINDOW HEAD	OMD 17
TERMINATION AT	OMD 18
WOOD FRAMED DECK	

Detail

TERMINATION AT	OMD 19
WATERPROOF DECK	
PREPARATION AT PARAPET/	OMD 20
WALL INTERSECTION	
TERMINATION AT PARAPET -	OMD 21
CAP FLASHING	
TERMINATION AT FLAT ROOF -	OMD 22
SOLID SUBSTRATE	
TERMINATION AT SLOPED ROOF	OMD 23
VERTICAL WALL/ SUSPENDED	OMD 24
SOFFIT TRANSITION	
TRANSITION AT SOFFIT/	OMD 25
FASCIA INTERSECTION	
FASCIA/ UNINSULATED SOFFIT	OMD 26
TRANSITION	
TERMINATION AT	OMD 27
UNINSULATED SOFFIT VENT	
HORIZONTAL JOINT AT SLIP TRACK	OMD 28
HORIZONTAL JOINT -	OMD 29
SUBSTRATE CHANGE	
HORIZONTAL TERMINATION	OMD 30
AT STONE VENEER	
HORIZONTAL TERMINATION	OMD 31
AT LAP SIDING	
VERTICAL EXPANSION JOINT -	OMD 32
EIFS	
THROUGH-WALL EXPANSION JOINT	OMD 33
THROUGH-WALL EXPANSION JOINT-	OMD 33a
DYMONIC SIMPLE SEAL OPTION	
VERTICAL EXPANSION JOINT -	OMD 34
FLUSH AND RECESSED OPTIONS	
VERTICAL EXPANSION JOINT -	OMD 35
DOUBLE SEAL OPTION	
VERTICAL TERMINATION	OMD 36
AT STONE VENEER	
PENETRATIONS	OMD 37
SIGN ATTACHMENT	OMD 38
AESTHETIC REVEALS	OMD 39
RECESSED GRAPHICS	OMD 40
PROJECTING GRAPHICS	OMD 41

NOTE:

DRYVIT AND TREMCO MAKES NO REPRESENTATION REGARDING CONFORMITY OF ITS SUGGESTIONS TO MODEL BUILDING CODES, ENGINEERING CRITERIA, SPECIFIC APPLICATIONS, OR PROJECT LOCATIONS. ALL COMPONENTS INDICATED IN ILLUSTRATIONS, AS WELL AS OTHERS THAT MAY BE REQUIRED FOR THE INTEGRITY OF THE SYSTEM SHALL BE DESIGNED, DETAILED, AND ENGINEERED BY REPRESENTATIVES OF THE ARCHITECT, OWNER, OR CONTRACTOR TO BE IN CONFORMANCE WITH MODEL CODES, ARCHITECTURAL, AND ENGINEERING REQUIREMENTS PERTAINING TO SPECIFIC BUILDING PROJECTS.

DRYVIT AND TREMCO MAKE NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ARCHITECTURAL DESIGN, ENGINEERING, OR WORKMANSHIP OF PROJECTS UTILIZING DRYVIT SYSTEMS OR PRODUCTS.

THE LIABILITIES OF DRYVIT AND TREMCO SHALL BE AS STATED IN THE DRYVIT STANDARD WARRANTY. CONTACT DRYVIT AND TREMCO FOR A FULL AND COMPLETE COPY OF THE WARRANTY.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

Outsulation® MD System®



Dryvit Technical Support: 800-556-7752

Detail: Table of Contents

Drawn by: KAB

Checked by: CB

Scale: NTS

Date: 1/2022

File Name:

TOC



Construction Products Group

www.tremcocpg.com