



- NOTES:**
1. USE OF THIS DETAIL IS LIMITED TO SLAB-ON-GRADE APPLICATIONS.
 2. INCORPORATE MEASURES TO PROTECT STRUCTURE FROM MOISTURE INTRUSION, DAMPNES, AND FROST HEAVE.
 3. TO PREVENT DEBRIS ACCUMULATION, IT IS RECOMMENDED TO TERMINATE SYSTEM 2" (51 MM) ABOVE SIDEWALK.
 4. DRYVIT CORNER MESH AND DRIVIT DETAIL MESH ARE EMBEDDED IN DRYVIT BASE COAT, NOT SHOWN FOR CLARITY. TRIM CORNER MESH TO FACE OF SUBSTRATE AS REQUIRED.

5. EXTEND DRYVIT STANDARD REINFORCING MESH ONTO EDGE OF EPS.
6. ENSURE BOTTOM EDGE OF DRAINAGE STRIP IS LEFT FREE TO DRAIN.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

Outsulation® HDCI™ System®

 Dryvit Technical Support: 800-556-7752	Detail: Termination at ADA Compliant Sidewalk - Tremco Dymonic 100/ Tremco Waterproofing Option				File Name: HDCI 11a		 Construction Products Group
	Drawn by: KAB	Checked by: CB	Scale: NTS	Date: 10/2021			
www.tremcocpg.com							