



**NOTE:**

1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD™ OR STANDARD PLUS™ MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
2. DIMENSIONS GREATER THAN 2'-0" (600 MM) REQUIRE SYSTEM CONFIGURATION SIMILAR TO WALL FACE.
3. TREMCO DYMONIC 100 AT 40 MILS MAYBE USED IN LIEU OF EXOAIR 110AT. APPLY DYMONIC 100 AT 40 MILS, 1" (25MM) MIN.ON SUBSTRATE FACE.
4. FOR ALTERNATIVE SEE DETAIL OPE 19 - PARAPET - SOLID SUBSTRATE WITH METAL COPING
5. REFER TO PRODUCT DATA SHEETS FOR SPECIFIC APPLICATION METHODS.
6. THE ONLY WRB TO BE USED WITH BACKSTOP FLASH AND FILL IS BACKSTOP® NTX™

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

**Outsulation® PE System™**

<p>Dryvit Technical Support: 800-556-7752</p>	Detail: Parapet - Solid Substrate with Metal Coping - Tremco ExoAir 110AT with Dymonic 100 Option			File Name:	<p>Construction Products Group</p>
	Drawn by: SMS	Checked by: CB	Scale: NTS	Date: 1/2022	
<a href="http://www.tremcocpg.com">www.tremcocpg.com</a>					