



TECHNICAL DATA SHEET

DRYVIT GRID TAPE™
DS450

DRYVIT GRID TAPE

PRODUCT DESCRIPTION

Dryvit Grid Tape is a specially woven and treated glass fiber mesh weighing 1.8 oz/yd² (61 g/m²) and which is self adhering. It is utilized in a variety of Dryvit systems, which require the joints and edges of the sheathing to be taped prior to the application of an air and moisture protective barrier such as Backstop NTX™.

PROPERTIES

Limitations: Dryvit Grid Tape is compatible with all cement board and gypsum based sheathings. Surface must be clean, dry and free from dust and other contaminants prior to adhering Grid Tape. Do not apply more Grid Tape than can be coated with air and moisture barrier in the same day.

Composition: Dryvit Grid Tape is a leno weave fiberglass product shipped in rolls 300 ft (91.4 m) long and 4 in (100 mm) wide and weighs 1.8 oz/yd² (61 g/m²).

SURFACE PREPARATION

Sheathing must be installed according to manufacturer's specifications. Surface must be smooth, clean, dry, and free from dust or any protrusions, which might hinder the regularity or adhesion of the Grid Tape.

APPLICATION

Center the Grid Tape on the sheathing board joints, edges, etc. with the pressure sensitive backing in contact with the sheathing surface. Press firmly into place and do not allow wrinkles to form in the tape.

STORAGE

Protect from elements, freezing and physical damage.

AVAILABILITY

Dryvit Grid Tape is available only from your Dryvit distributor.

TECHNICAL AND FIELD SERVICES

Available upon request.

Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of Dryvit products as of the date of publication of this document and is presented in good faith. Dryvit assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Dryvit.

For more information on Dryvit or Continuous Insulation, [click here](#).

Printed in USA. Issued 1.1.2022

©Dryvit 2022

DS450

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



dryvit.com | 800.556.7752



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com